752 Compact



Self Adhesive C-Wrap Labelling Machine.


The HERMA 752 automatically applies in one pass, a three-panel label to the top, front (leading face) and base of a wide range of trays such as those used in the fresh meat, produce and ready meals industries.

The 752 is quick and easy to change from one pack size to another, even in the busiest of production environments. The simple design and high build quality of the system ensures that it is suitable for use in most production environments. Operating speeds vary and are dependent upon the length of the label being applied, the pack length and direction of travel and when fitted with a unit from our range of optional thermal transfer printers, the standard system is capable of printing and applying labels that carry fixed weight information.

- By adjusting the width of the in-feed guide rails, side belts and the position of the label applicator the system is ready to accept a new pack size in minutes.
- The length of the variable speed conveyors can be tailored to suit the specific requirements for example; gaps in existing production lines.
- A wide range of ancillary add on options including a reliable and efficient pack turning unit, ensures that the HERMA 752 is the most flexible and cost effective three panel labelling system available.
- For a relatively small on cost the system can be configured to print catch weight data supplied from most catch weight weighing systems.



The Ultimate C Wrap Labelling System



The advantages of HERMA 400 models at a glance:

- > Control integrated into the applicator no separate control box required
- > Clearly laid out operating panel
- > Wide range power input 100AC...240V AC +/- 10%, 50 Hz...60Hz
- > Automatic synchronisation of labelling and product speeds
- > Special unwind unit giving consistent web tension
- > Comprehensive range of modules: pedestals, label sensors, printing and embossing units always a perfect fit
- > Available as left-hand and right-hand versions, for upright, horizontal or suspended operation, width in increments of 80 mm/3" up to 320mm/12"
- > Configured for PLC connection
- > Transparent label sensing available as standard
- > Integration with the most coders/printers



AIS (Automatic Identification Systems) Ltd Unit 48 Canal Walk Park West Ind Park Nangor Road Dublin 12, Ireland

Tel: +353 (0)1 6205742 NI: (028) 90718912 Mob: 086 8508146 Fax: +353 (0)1 6205735

We are constantly improving our products, therefore all technical data is subject to change without prior notice.